

evs

Key Features



Name FTS 60 - version 2.0 Version Instant Bandracturer Reavendors Industries SPA Overview: - NESCAFE® Name FTS 60 - version 2.0 Version Instant Bandracturer Reavendors Industries SPA Overview: - NESCAFE® - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industries SPA Overview: - NescarE Trs 80 - neurodors Industriem SPA Overview:				
Branding NESCAFÉ® Manufacturer Rheavendors industries SPA Overview: • • • • • • • • • • • • • • • • • • •	NESCAFÉ		Name	FTS 60 - version 2.0
Branding NESCAFE [®] Manufacturer Rheavendors Industries SPA Overview: • SEGAFE FTS 40 is the updated machine model for soluble ingredients Image: Segaration of the segaration of soluble ingredients • SEGAFE FTS 40 is the updated machine model for soluble ingredients Image: Segaration of Segaratio Segaration of Segaration of Segaration of Segaratio Seg		Nescori	Version	Instant
Dimensions (Footprint) Construction of the standard of		Espresso Double Espresso Lungo	Branding	NESCAFÉ®
	Het Choosen	nu visite Learning Her Water	Manufacturer	Rheavendors Industries SPA
2020. Description Dimensions (Footprint) Standard contilers version Paiph			Overview:	
Dimensions (FoOp/in!) The It' fourth screen is new clubbed with a trand new user interface that unclease hard has been introduced to accommode different Cup kees tech, and Autobie Cup starts. Dimensions (FoOp/in!) The mechanic can additionally be configured with the following options: Sindad canifers version Height Depth 58.2 kg Weight (Net) 28.2 kg Weight (Net) 38.2 kg Weight (Net) 28.2 kg Weight (Cos) 39.2 kg Dispess Area Cup station options Normed conitiers 4.5 dr of type options Veight (Cos) 39.2 kg Dispess Area Cup station options Normed regist 4.1 k. J. C. K. E. L. G er M Number of canitiers 4.1 k. J. C. K. E. L. G er M Number of canitiers 4.5 dr of type options Side sported protocal station options A. L. B. J. C. K. E. L. G er M Number of canitiers 4.5 dr of type optional Signadiations A. L. B. J. C. K. E. L. G er M Number of canitiers 4.5 dr of type of canitig Signadiations A. L. B. J. C. K. E. L. G er M Number of canitiers				is the updated machine model for from Q2
Interface that unlocks new features such as cup customization (g. Adding an additionally be configured with the following options: Dimensions (Footprint) Standard canisters version Height 6.0.0 cm Deth 5.86 cm Veright (Net) 28.2 kg Viriation (g. Adding an additionally be configured with the following options: - Side Hot Water Cutlet. Technical Interface 2.30 V Prequency 50/40 Hz Veright (Net) 28.2 kg Veright (Net) 28.2 kg Veright (Net) 28.2 kg Veright (Net) 28.2 kg Veright (Net) 29.2 kg Namual languages English (Phinted formet) Maximal Interface Namual Languages Payment system N/A (If needed, order separately: module on change giver) Naminal Interface Namber of selections Number of mixers 2 ord - Standard canisters 4,5 ord			that can deliver you to target c	great quality coffee, cup after cup, allowing
Dimensions (Foolprint) - Side Hol Water Outlet. Dimensions (Foolprint) - Side Hol Water Outlet. Standard canisters version - Voltage Depth 6.8.8 cm Weight (Net) 28.2 kg Weight (Gross) 3.1.6 kg Telerentises version - Voltage Height 67.2 cm Weight (Gross) 3.0.8 kg Dignese Area Other languages to specify (Adaitonal cost is opplied) Maximal height 14.6 cm Maximal faight 14.6 cm Number of consisters 4, 5 or 6 Vimber of consisters 4, 5 or 6 Number of consisters 4, 5 or 6 Number of consisters 2 or 3 Poer Consisters 2 or 3 Proce Consisters 2 or 3 Proce Consisters 2 or 3 Number of consisters 2 or 3 Proce Consisters 2 or 3 Number of nikers <			interface tha customization (e different cup siz	t unlocks new features such as cup eg. Adding an additional shot of espresso, res etc.). An Adjustable cup stand has been
Standard canisters version Voltage 230 V Height 60.0 cm Frequency 50/60 Hz Width 42.2 cm Water connection 3/8 gas Weight (Gross) 31.0 kg Water connection 3/8 gas Toller conisters version Frequency 0.1 - 0.8 Mpa Height 67.2 cm Water connection SW for NP telemetry Manual languages English (Printed format) Digital format available in Italian, Prench, Spanish and German Depth 56.8 cm Other languages to specify (Additional cest is applied) Water connection SW for NP telemetry Manual languages English (Printed format) Dispense Area Maximal height 14.6 cm Maximal height 14.6 cm Supported protocol Parallel/(EX/MDB Display Yes, fouch screen Menu Languages English (Standard) Other languages to specify (Additional cest is applied) Menu Languages English (Standard) Configurations A, L, B, J, C, K, E, L, G or M Number of selections Depending on configuration Number of canisters 4, S or 6 Number of selections Depending on configuration Number of canisters 2 or 3 Standard Colors and branding Nestlé specific information			following option:	s:
Height 60.0 cm Depth 56.8 cm Weight (Net) 28.2 kg Weight (Cross) 31.0 kg Toller conisters version 67.2 cm Depth 56.8 cm Depth 56.8 cm Weight (Net) 29.2 kg Weight (Net) 52.2 kg Weight (Net) 52.2 kg Weight (Net) 52.2 kg Weight (Strips) 32.0 kg Dispense Area Maximal height Maximal height 14.6 cm Maximal height 14.6 cm Mumber of canisters 4.5 or 6 Stondard canisters 5.5 or 6 Number of canisters 4.5 or 6 Number of canisters 4.5 or 6 Number of canisters 2 or 3 Power Consumption 1700 wg Boiler Capacity 3.4 Lt Direct Hot Water Optional Autoneon/inse facility Yes Veriation B and J Autoneon/inse facility Autoneon/inse facility Yes Yersion Plumbed / Unplumbed Veriation B cond J Number of tankers Candiguration B and J 10.1" Puret No. Standard (Or other to specify) Yersion Plumbed / Unplu	Dimensions (Footprin	nt)	Technical Interf	ace
Depth 568 cm Width 422 cm Width 422 cm Weight (Net) 282 kg Weight (Gross) 310 kg Taller canisters version 672 cm Height 672 cm Depth 568 cm Weight (Net) 292 kg Weight (Net) 292 kg Weight (Gross) 320 kg Dispense Area Maximal lameter Cup station pen Menu Languages Beverage Processing English (Printed format) Configurations A, L, B, J, C, K, E, L, G or M Number of canisters A, S or 6 Type of canisters 4, 5 or 6 Number of canisters 2 or 3 Power Consumption 1700 W Bolier Capacity 3,4 Lt Direct Hot Water Yes (standard) Configurations and J No, except for Auto clean/rinse facility Yes (standard) Configurations and J No, except for Auto clean/rinse facility Yes (standard) Configu		n	Voltage	230 V
Width 42.2 cm Wolfer connection 3/8 gas Weight (Net) 28.2 kg Water pressure 0.1-0.8 Mpc Taller canisters version Telemetry connection SW for NP telemetry Manual languages English (Printed format) Dight 67.2 cm Weight (Ket) 29.2 kg Weight (Cross) 32.0 kg Dispense Area N/A (If needed, order separately: module on change giver) Maximal height 14.6 cm Mumber of canisters 4.1 kg, J. C. K. E. L. G or M Number of canisters 4.5 or 6 Type of canisters 2 or 3 Power Cansumption 1700 wf Boiler Capacity 3.4 Lt Auto clean/rise for and J Auto clean/rise for and J Auto clean/rise for and J Auto clean/rise for and J Auto clean/rise for and J Configurations Auto clean/rise for and J Ye set Auto clean/rise for and J <td>•</td> <td></td> <td></td> <td></td>	•			
Weight (Net) 28.2 kg Weight (Gross) 31.0 kg Teller conisters version Telementry connection Height 67.2 cm Depth 5.6 cm Weight (Net) 29.2 kg Weight (Gross) 32.0 kg Weight (Gross) 32.0 kg Weight (Gross) 29.2 kg Payment system N/A (if needed, order separately: Maximal height 14.6 cm Maximal height 14.6 cm Number of canisters 4, 5 or 6 Type of canisters 4, 5 or 6 Number of canisters 4, 5 or 6 Number of nikers 2 or 3 Power Consumption 1700 w Boiler Capacity 34.1 t Oxfler capacity 34.1 t Outher languages Laccally managed Number of nikers 2 or 3 Power Consumption 1700 w Boiler Capacity 34.1 t </td <td></td> <td></td> <td></td> <td></td>				
Weight (Gross) 31.0 kg Telemetry connection SW for NP telemetry Taller canisters version Fight 67.2 cm English (Printed format) Height 67.2 cm Digital format available in Italian, French, Spanish and German Other languages to specify (Additional cest is applied) Weight (Net) 29.2 kg Other languages to specify (Additional cest is applied) Dispense Area Maximal height 14.4 cm Maximal height 14.4 cm Supported protocol Parallel/EKE/MDB Display Yes, touch screen Menu Languages English (Standard) Configurations A. I. B. J. C. K. E. L. G or M Other languages to specify (Additional cest is applied) Number of canisters 2 or 3 Parallel/EKE/MDB Number of mixers 2 or 3 Poer cansumption 1700 w Boiler Capacity 3.4 Lt Standard Optional Auto clean/rinse facility Yes (standard) Celors and branding NESCAFE [®] Black Number of mixers 2 or 3 Poer facility Yes Yes for display No, except for Colors and branding NESCAFE [®] Black Number of inkers Cell (Growing table) Standard (Or other to specify) Yes for display No, except for Colors and branding NESCAFE [®] Black		28.2 kg		
Tuller canisters version English (Printed format) Height 67.2 cm Depth 56.8 cm Width 42.2 cm Weight (Gross) 32.0 kg Dispense Area N/A (If needed, order separately: Maximal height 14.6 cm Mumber of canisters 4, 5 or 6 Yue of canisters 4, 5 or 6 Number of anisters 4, 5 or 6 Number of mixers 2 or 3 Poier Cansumption 1700 W Boiler Capacity 3.4.1 Direct Hot Water Yes (standard) Auto clean/rinse facility Yes Front display Yes Yersion Pulmbed / Unplumbed (available only in 14.2 configuration Standard (Gr other to specify) Yersion Pulmbed / Unplumbed Yersion Pulmbed / Unplumbed Yersion Pulmbed / Unplumbed Yersion <t< td=""><td>Weight (Gross)</td><td>31.0 kg</td><td>Telemetry connection</td><td>on SW for NP telemetry</td></t<>	Weight (Gross)	31.0 kg	Telemetry connection	on SW for NP telemetry
Height 67.2 cm Depth 56.8 cm Width 42.2 cm Weight (Ixet) 29.2 kg Weight (Gross) 32.0 kg Dispense Area Maximal height Maximal height 14.6 cm Maximal height 14.6 cm Maximal height 14.6 cm Maximal height 14.6 cm Maximal diameter Cup station open Beverage Processing English (Standard) Configurations A, I, B, J, C, K, E, L, G or M Number of canisters 4, 5 or 6 Type of canisters 4, 5 or 6 Number of strests 2 or 3 Power Consumption 1700 w Boiler Capacity 3,4,1 th Direct Hot Water Yes (standard) Step cation band J Colors and branding Auto chean/rinse facility Yes Front display 10,1 ^m Version Plumbed / Unplumbed (available only in 14.42 configuration Standard (Or other to specify) Packing labels Standard (Or other to specify) Packing labels<	Taller canisters version		Manual languages	English (Printed format)
Depth 56.8 cm Other languages to specify (Additional cost is applied) Width 42.2 cm Customer Interface Weight (Net) 29.2 kg Payment system N/A (if needed, order separately: module on change giver) Dispense Area Maximal height 14.6 cm Supported protocol Parallel/EXE/MDB Maximal diameter Cup station open Display Yes, touch screen Beverage Processing English (Standard) Configurations A. J. B. J. C. K. E. L. G or M Other languages to specify (Additional cost is applied) Number of canisters 4, 5 or 6 Memu Languages English (Standard) Other languages to specify (Additional cost is applied) Number of selections up to 48 Number of mixers 2 or 3 Selection labels Locally managed Biler Capacity 3,4 Lt Diforal Number of preselections Depending on configuration Side separated hot water Optional Nestlé specific information Celors and branding NESCAFÉ® Black Outer languages Standard (Or other to specify) Yes Packing labels Standard (Or other to specify) Power Consumption 1700 wt Refice Nestlé specific information Celors and branding Celors and branding Custo capacity 0,1 m <td></td> <td>67.2 cm</td> <td>Diaital format av</td> <td></td>		67.2 cm	Diaital format av	
Weight (Net) 29.2 kg Customer Interface Weight (Gross) 32.0 kg Payment system N/A (if needed, order separately: module on change giver) Dispense Area Payment system N/A (if needed, order separately: module on change giver) Maximal height 14.6 cm Supported protocol Paralle/JCKZ/MDB Maximal diameter Cup station open Supported protocol Paralle/JCKZ/MDB Display Yes, touch screen Menu Languages English (Standard) Number of canisters A. J, B. J, C, K, E, L, G or M Number of selections up to 48 Number of canisters 4, 5 or 6 Number of selections up to 48 Number of nisters 2 or 3 Power Consumption 1700 w Selection labels Locally managed Number of mixers 2 or 3 Pranding NESCAFÉ [®] Black Nestlé specific information Colors and branding NESCAFÉ [®] Black Certifications CE-CB (Or other to specify) Auto clean/rinse facility Yes Yes Standard (Or other to specify) Yersion Plumbed / Unplumbed Plumbed / Unplumbed Standard (Or other to specify) Yersion Plumbed / Un				
Weight (Gross) 32.0 kg Payment system N/A (if needed, order separately: module on change giver) Dispense Area Maximal height 14.6 cm Maximal height 14.6 cm Supported protocol Parallel/EXE/MDB Beverage Processing English (Standard) Configurations A. I, B. J. C. K. E. L. G or M Other languages to specify (Additional cost is applied Number of canisters 4, 5 or 6 Other languages to specify (Additional cost is applied Number of ranisters 0 ranisters up to 48 Number of mixers 2 or 3 Parantening Power Consumption 1700 W Selection labels Locally managed Biler Capacity 3.4.1 Optional Number of preselections Depending on configuration Side separated hot water Optional Optional Nestlé specific information Configuration 8 and J No, except for Nestlé specific information Configuration 8 and J No, except for Certifications CE-CB (Or other to specify) Yersion Plumbed / Unplumbed Standard (Or other to specify) Packing labels Standard (Or other to specify) Version Plumbed / Unplumbed Information Certifications CE-CB (Or other to specify)			Customor Interf	
Dispense Area Maximal height 14.6 cm Maximal height 14.6 cm Maximal diameter Cup station open Beverage Processing Supported protocol Configurations A, I, B, J, C, K, E, L, G or M Number of canisters 4, 5 or 6 Type of canisters 4, 5 or 6 Number of canisters 2 or 3 Power Consumption 1700 W Direct Hot Water Yes (standard) Direct Hot Water Yes (standard) Colors and branding NESCAFÉ® Black Number of sale cliny Yes (standard) Side separated hot water Optional Auto clean/rinse facility Yes Yersion Plumbed / Unplumbed (available only in 14 A2 configuration) 10.1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) 10.1"				
Maximal height14.6 cmSupported protocolParallel/EXE/MDBMaximal diameterCup station openDisplayYes, touch screenBeverage ProcessingEnglish (Standard)ConfigurationsA, I, B, J, C, K, E, L, G or MMenu LanguagesEnglish (Standard)Number of canisters4, 5 or 6Number of selectionsDepending on configuration- Standard canisters2 or 3Power Consumption1700 W- Taller canisters2 or 3BrandingPower Consumption1700 WBrandingNESCAFÉ® BlackDirect Hot WaterYes (standard)Colors and brandingNESCAFÉ® BlackDirect Hot WaterYes (standard)CertificationsCE-CB (Or other to specify)Auto clean/rinse facilityYesStandard (Or other to specify)VersionPlumbed / UnplumbedYesStandard (Or other to specify)PackPacement No.Date:12.2019				module on change giver)
Beverage Processing Menu Languages Configurations A, I, B, J, C, K, E, L, G or M. Number of canisters 4, 5 or 6 Type of canisters 4, 5 or 6 - Standard canisters - Standard canisters - Taller canisters 2 or 3 Number of mixers 2 or 3 Power Consumption 1700 W Boiler Capacity 3,4 Lt Direct Hot Water Yes (standard) Side separated hot water Optional Auto clean/rinse facility Yes Front display 10,1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Standard (Or other to specify) Packing labels Standard (Or other to specify) * Information not available when document created. Will be added in later version	Maximal height			
Beverage Processing English (Standard) Configurations A, I, B, J, C, K, E, L, G or M Number of canisters 4, 5 or 6 Type of canisters 4, 5 or 6 Standard canisters 4, 5 or 6 - Taller canisters 2 or 3 Power Consumption 1700 W Boiler Capacity 3,4 Lt Direct Hot Water Yes (standard) Side separated hot water Optional Auto clean/rinse facility Yes Front display 10,1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Plumbed / Unplumbed * Information net available when document created. Will be added in later version	Maximal diameter	Cup station open		Yes, touch screen
ConfigurationsA, I, B, J, C, K, E, L, G or MOther languages to specify (Additional cost is appliedNumber of canisters4, 5 or 6Type of canisters4, 5 or 6Standard canisters4, 5 or 6- Taller canisters2 or 3Power of mixers2 or 3Power Consumption1700 WBoiler Capacity3, 4 LtDirect Hot WaterYes (standard)Side separated hot waterOptionalAutonomous Water TankNo, except forConfiguration B and JYesAuto clean/rinse facilityYesFront display10,1"VersionPlumbed / UnplumbedImage: Document No.Date:Image: Document No.Date:Image: Document No.Image: Document No.	Beverage Processing	g	Menu Languages	English (Standard)
Type of canistersNumber of selectionsup to 48Standard canistersTaller canistersNumber of preselectionsDepending on configurationNumber of mixers2 or 3Selection labelsLocally managedNumber of mixers2 or 3BrandingColors and brandingNESCAFÉ® BlackDirect Hot WaterYes (standard)OptionalNestlé specific informationNestlé specific informationAutonomous Water TankNo, except forCertificationsCE-CB (Or other to specify)Pront display10.1"YesStandard (Or other to specify)VersionPlumbed / UnplumbedInformation not available when document created. Will be added in later versionDocument No.Date:12.2019	•		Othe	
 Standard canisters Taller canisters Number of mixers 2 or 3 Power Consumption Boiler Capacity Standard value Standard canisters Number of preselections Depending on configuration Selection labels Locally managed Branding Colors and branding NESCAFÉ[®] Black Nestlé specific information Certifications Cerce (available only in 14 A2 configuration) Pocument No. 		4, 5 or 6	Number of coloration	
- Taller canisters Selection labels Locally managed Number of mixers 2 or 3 Power Consumption 1700 W Power Consumption 1700 W Branding Direct Hot Water Yes (standard) Direct Hot Water Yes (standard) Optional NESCAFÉ® Black Auto clean/rinse facility Yes Yes Front display 10.1" Certifications CE-CB (Or other to specify) Packing labels Standard (Or other to specify) Packing labels Standard (Or other to specify) Version Plumbed / Unplumbed Information not available when document created. Will be added in later version				
Power Consumption 1700 W Boiler Capacity 3,4 Lt Direct Hot Water Yes (standard) Side separated hot water Optional Autonomous Water Tank No, except for Configuration B and J Yes Auto clean/rinse facility Yes Front display 10,1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Dete: Document No. Date: Iter to the tool Dete: Iter to tool Date: Iter tool Dete: Iter tool Dete: Iter tool Date: Iter tool Date:				
Boiler Capacity 3,4 Lt Direct Hot Water 3,4 Lt Direct Hot Water Yes (standard) Side separated hot water Optional Autonomous Water Tank No, except for Configuration B and J Yes Auto clean/rinse facility Yes Front display 10.1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Dete: Document No. Date: Image: Document No. Date:			Branding	
Direct Hot Water Yes (standard) Side separated hot water Optional Autonomous Water Tank No, except for Configuration B and J Yes Auto clean/rinse facility Yes Front display 10.1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Certification not available when document created. Will be added in later version Document No. Date: 12.2019			Branaing	
Side separated hot water Optional Autonomous Water Tank No, except for Configuration B and J No, except for Auto clean/rinse facility Yes Front display 10.1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Certification not available when document created. Will be added in later version Document No. Date: 12.2019			Colors and branding	g NESCAFÉ [®] Black
Autonomous Water Tank No, except for Configuration B and J Vestific ations Auto clean/rinse facility Yes Front display 10.1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) The formation not available when document created. Will be added in later version Document No. Date: 12.2019				
Conliguration B and J Auto clean/rinse facility Front display Version Plumbed / Unplumbed (available only in 14 A2 configuration) Document No. Document No.	Autonomous Water Tank		Nestlé specific i	nformation
Action clearly in rise facility rises Front display 10.1" Version Plumbed / Unplumbed (available only in 14 A2 configuration) Packing labels Standard (Or other to specify) * Information not available when document created. Will be added in later version Document No. Date:	•	Vaa		
Version Plumbed / Unplumbed (available only in 14 A2 configuration) * Information not available when document created. Will be added in later version Document No. Date: 12.2019				
Document No. Date: 12.2019		Plumbed / Unplumbed		
		(available only in 14 A2 configuration)	* Information not available	when document created. Will be added in later version
		Document No.	Dat	e: 12.2019

 Ref:
 Table Top/FTS60 I v.2 / Dispenser
 Target:
 Topic:
 Commercial

 This document and its contents are property of EVS and Nestlé SA and shall not be reproduced without permission.
 Commercial
 Commercial





Accessories


- Top + unibase cabinet spacer
- Unibase cabinet shelf metal
- Immersion pump kit

evs

- modul<on Cups LD/LD/C80/C80
- modul<on Water W/W-L or W/W-R
- modul<on Change giver
- Unibase Metal Cabinet
- Recessed drip tray
- Side panel advertisement
- Back panel advertisement

Standard configurations

- Configuration A0:
 - 4 instant canisters, 2 mixers, hot water, plumbed.



	MENU					
1	Espresso	7	Latte Macchiato			
2	Lungo	8	Mocaccino			
3	Macchiato	9	Chocolate			
4	Short White Coffee	10	Strong Chocolate			
5	Cappuccino	11	Chocomilk			
6	Latte	12	Hot Water			

Configuration I0:

4

5


6

Short white coffee

Cappuccino

Latte

- 4 instant canisters, 2 mixers, hot water, side hot water, plumbed.



10

11

12

Strong chocolate

Chocomilk

Hot Water

Default features

- Adjustable Cup Stand
- New Fusion 2 firmware
- New HMI layout (including cup customization)
- Color coding of pipes

Optional features

Side Hot Water Outlet

2. NESCAFÉ[®] (tall canisters version)



	Document No.		Date:	12.2019		
Ref:	Table Top/ FTS60 I v.2/ Dispenser Target:		Topic:	Commercial		
This o	This document and its contents are property of EVS and Nestlé SA and shall not be reproduced without permission.					






• Configuration BO:

evs


- 4 instant canisters, 2 mixers, hot water, unplumbed.



	MENU				
1	Espresso	7	Latte Macchiato		
2	Lungo	8	Mocaccino		
3	Macchiato	9	Chocolate		
4	Short White Coffee	10	Strong Chocolate		
5	Cappuccino	11	Chocomilk		
6	Latte	12	Hot Water		

• Configuration J0:


- 4 instant canisters, 2 mixers, hot water, separated side hot water, unplumbed.



	MENU					
1	Espresso	7	Latte macchiato			
2	Lungo	8	Moccaccino			
3	Macchiato	9	Chocolate			
4	Short white coffee	10	Strong chocolate			
5	Cappuccino	11	Chocomilk			
6	Latte	12	Hot Water			

• Configuration C0:


- 4 instant canisters, 3 mixers, hot water, plumbed.



	MENU					
1	Espresso	7	Moccaccino			
2	Lungo	8	Chocolate			
3	Macchiato	9	Strong Chocolate			
4	Cappuccino	10	Chocomilk			
5	Latte	11	Decaffeinated			
6	Latte Macchiato	12	Hot Water			

Configuration K0:

- 4 instant canisters, 3 mixers, hot water, side separated hot water, plumbed



	MENU					
1	Espresso	7	Moccaccino			
2	Lungo	8	Chocolate			
3	Macchiato	9	Strong chocolate			
4	Cappuccino	10	Chocomilk			
5	Latte	11	Decaffeinated			
6	Latte macchiato	12	Hot Water			

Document No.			12.2019
Ref: Table Top/ FTS60 v.2 / Dispenser	Target:	Topic:	Commercial
This document and its contents are property of EVS a	nd Nestlé SA and shall not be r	reproduced	without permission.






Configuration E0:

evs


- 5 instant canisters, 3 mixers, hot water, plumbed.



	MENU					
1	Espresso	7	Mocha			
2	Lungo	8	Chocolate			
3	Short White Coffee	9	Strong Chocolate			
4	Cappuccino	10	Chocomilk			
5	Latte	11	Теа			
6	Macchiato	12	Hot Water			

• Configuration LO:


- 5 instant canisters, 3 mixers, hot water, side separated hot water, plumbed.



	MENU				
1	Espresso	7	Mocha		
2	Lungo	8	Chocolate		
3	Short white coffee	9	Strong chocolate		
4	Cappuccino	10	Chocomilk		
5	Latte	11	Теа		
6	Latte macchiato	12	Hot Water		

Configuration G0:


- 6 instant canisters, 3 mixers, hot water, plumbed.



	MENU				
1	Espresso	7	Chocolate		
2	Lungo	8	Strong Chocolate		
3	Macchiato	9	Chocomilk		
4	Short white coffee	10	Tea 1		
5	Cappuccino	11	Tea 2		
6	Latte	12	Hot Water		

Configuration M0:

- 6 instant canisters, 3 mixers, hot water, side separated hot water , plumbed.



	MENU				
1	Espresso	7	Chocolate		
2	Lungo	8	Strong chocolate		
3	Macchiato	9	Chocomilk		
4	Short white coffee	10	Tea 1		
5	Cappuccino	11	Tea 2		
6	Latte	12	Hot Water		

Document No.		Date:	12.2019	
Ref:	Table Top/ FTS60 v.2 / Dispenser	Target:	Topic:	Commercial
This document and its contents are property of EVS and Nestlé SA and shall not be reproduced without permission.				





Dimensions - Standard canisters

evs

Boxed machine (1 machine & outer cartons)

Height	67.4 cm
Width	45.4 cm
Depth	59.4 cm

Sea freight Palletized Dimensions (1 pallet - 12 units)

Height	217.2 cm
Width	120.0 cm
Depth	94.0 cm
20' (10 pallets x 12 units)	120 units

20' (10 pallets x 12 units) 40' (22 pallets x 12 units) High Cube (22 pallets x 12 units)

Airfreight Palletized Dimensions (1 pallet - 8 units)

Full Truck

28 pallets x 12 units

336 units

176 units

264 units

264 units

Dimensions - Taller canisters

High Cube (22 pallets x 8 units)

Boxed machine (1 machine & outer cartons)

Height	77.9 cm
Width	45.4 cm
Depth	59.4 cm

Sea freight Palletized Dimensions (1 pallet - 8 units)

Height	170.8 cm
Width	120.0 cm
Depth	94.0 cm
20' (10 pallets x 8 units)	80 units
40' (22 pallets x 8 units)	176 units

Airfreight Palletized Dimensions (1 pallet - 4 units)

Height Width Depth Full Truck	92.9 cm 120.0 cm 94.0 cm
28 pallets x 8 units	224 units

28 pallets x 8 units

Docu	ment No.		Date:	12.2019
Ref:	Table Top/ FTS60 I v.2 / Dispenser	Target:	Topic:	Commercial
This document and its contents are property of EVS and Nestlé SA and shall not be reproduced without permission.				